

CE Thermal Vision



www.CEthermal.com

Shenzhen Chengen Thermovision Technology Co., Ltd.

Chengen founded in 2015, is a high-tech enterprise specializing in thermal imaging products. Since its inception, Chengen has been deeply dedicated to the field of infrared thermal imaging, investing heavily in the development of a wide range of thermal imaging devices. Through years of continuous innovation, the company has accumulated extensive technical expertise and built an outstanding R&D team with rich development experience, providing strong support for business operations. Today, Chengen possesses advanced and mature technologies, enabling the development and production of high-performance , reliable products , and is capable of offering comprehensive OEM and ODM services to its clients.



2 *Factory buildings*

13000m² *Factory area*

350+ *Staff*



TK-C Series Thermal Imaging Sight Scope

Product Features

Detector Resolution	Pixel Pitch
256 / 384 / 640	12μm
Lens	Frame Rate
25/ 35 /50mm	50Hz
Digital Zoom	NETD
1x~8x	< 35mK

Size	Pseudo-color Modes
144x86x63mm/ 155x86x63mm 170x86x63mm	White Hot , Black Hot, Red Hot, Iron Red, etc.

Model	TK-C225	TK-C335	TK-C350	TK-C635	TK-C650
Focal Length (mm)	25	35	50	35	50
FOV	7x5.3°	7.5x5.7°	5.3x4°	5.3x4°	8.8x7°
Detection Distance	2500m	3500m	5000m	3500m	5000m
Recognition Distance	625m	875m	1250m	875m	1250m
Identification Distance	313m	438m	625m	438m	625m
Detector Resolution	256x192, 12μm	384x288, 12μm	384x288, 12μm	640x512, 12μm	640x512, 12μm
Display Resolution	OLED 0.32 800x600	OLED 0.39 1024x768	OLED 0.39 1024x768	OLED 0.39 1024x768	OLED 0.39 1024x768
NETD	<25mK	<35mK	<35mK	<35mK	<35mK
Detector Type	Uncooled Focal Plane Array Detector (VOX - Vanadium Oxide)				
Spectral Response	8-14μm				
Frame Rate	50Hz				
Button Operation	2 Buttons + 1 Rotary Encoder				
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.				
Digital Zoom	1X-8X Zoom				
Shutter Mode	Manual, Auto Shutter				
Function Menu	NUC, Digital Filtering and Noise Reduction, Crosshair, WIFI Hotspot, Photo and Video Recording, Laser Rangefinder, Auto Power-off, Restore Default Settings, DDE, Removable Battery, Version Information, Gyroscope, Blind Pixel Calibration, Ballistic Calculation, Accelerometer, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode, Image Super-Resolution (SR).				
Battery Capacity	Single Cell 18650 / 3400mAh				
Storage Memory	32G				
Operating Time	5H(Individual Observation Time)				
IP Rating	IP66				
Shock	1000g				
Weight (Including Battery)	551g	592g	669g	592g	669g
Size	144x86x63mm	155x86x63mm	170x86x63mm	155x86x63mm	170x86x63mm
Housing Material	Metal				
Operating Environment	-20C° ~ +60C°				



TK-T Series Thermal Imaging Sight Scope

Product Features

Detector Resolution 256x192	Pixel Pitch 12µm
Lens 25mm	Frame Rate 50Hz
Digital Zoom 1x-8x	NETD < 25mK
Size 141x83x57mm	Pseudo-color Modes White Hot , Black Hot, Red Hot, Iron Red, etc.

Model	TK-T225
Focal Length (mm)	25
FOV	7x5.3°
Detection Distance	2500m
Recognition Distance	625m
Identification Distance	313m
Detector Resolution	256x192, 12µm
Display Resolution	OLED 0.32 800x600
NETD	< 25mK
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)
Spectral Response	8-14µm
Frame Rate	50Hz
Button Operation	2 Buttons + 1 Rotary Encoder
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.
Digital Zoom	1X - 8X Zoom
Shutter Mode	Manual, Auto Shutter
Function Menu	NUC, Digital Filtering and Noise Reduction, Crosshair, WIFI Hotspot, Photo and Video Recording, Laser Rangefinder, Auto Power-off, Restore Default Settings, DDE, Removable Battery, Version Information, Gyroscope, Blind Pixel Calibration, Ballistic Calculation, Accelerometer, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode, Image Super-Resolution (SR).
Battery Capacity	Single Cell 18650 / 3400mAh
Storage Memory	32G
Operating Time	5H (Individual Observation Time)
IP Rating	IP66
Shock	1000g
Weight (Including Battery)	488g
Size	141x83x57mm
Housing Material	Metal
Operating Environment	-20C° ~ +60C°



ZS Series Thermal Imaging Sight Scope

Product Features

Detector Resolution
384x288 / 640x512

Lens
25 / 35 / 50mm

Digital Zoom
1x-8x

Size
137x91x65mm / 178x91x65mm
185x91x65mm

Pixel Pitch
12μm

Frame Rate
50Hz

NETD
< 35mK

Pseudo-color Modes
White Hot , Black Hot, Red Hot, Iron Red, etc.

Model	ZS325	ZS335	ZS350	ZS635	ZS650
Focal Length (mm)	25	35	50	35	50
FOV	10.5x7.9°	7.5x5.7°	5.3x4°	5.3x4°	8.8x7°
Detection Distance	2500m	3500m	5000m	3500m	5000m
Recognition Distance	625m	875m	1250m	875m	1250m
Identification Distance	313m	438m	625m	438m	625m
Detector Resolution	384x288, 12μm			640x512, 12μm	
Display Resolution	OLED 0.39 1024x768				
NETD	< 35mK (@25°C,F#=1.0)				
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)				
Spectral Response	8-14μm				
Frame Rate	50Hz				
Button Operation	2 Buttons + 1 Encoder				
Pseudo-color Modes	White Hot , Black Hot, Red Hot, Iron Red, etc.				
Digital Zoom	1X-8X Zoom				
Shutter Mode	Manual, Auto Shutter				
Function Menu	NUC, Digital Filtering and Noise Reduction, Crosshair, WIFI Hotspot, Photo and Video Recording, Laser Rangefinder, Restore Default Settings, Removable Battery, Version Information, DDE, Gyroscope, Blind Pixel Calibration, Ballistic Calculation, Accelerometer, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode, Clip-on Mode.				
Battery Capacity	Single Cell 18650 / 3400mAh				
Storage Memory	32G				
Operating Time	5H(Individual Observation Time)				
IP Rating	IP66				
Shock	1000g				
Weight (Including Battery)	597g	638g	708g	638g	708g
Size	137x91x65mm	178x91x65mm	185x91x65mm	178x91x65mm	185x91x65mm
Housing Material	Metal				
Operating Environment	-20C° ~ +60C°				



TB Series Thermal Imaging Sight Scope

Product Features

Detector Resolution
384x288/640x512

Lens
35 / 50mm

Digital Zoom
1x-8x

Size
134x80x62mm

Pixel Pitch
12μm

Frame Rate
50Hz

NETD
< 35mK

Pseudo-color Modes
White Hot , Black Hot,
Red Hot, Iron Red, etc.

Model	TB335	TB350	TB635	TB650
Focal Length (mm)	35	50	35	50
FOV	7.5x5.7°	5.3x4°	5.3x4°	8.8x7°
Detection Distance	3500m	5000m	3500m	5000m
Recognition Distance	875m	1250m	875m	1250m
Identification Distance	438m	625m	438m	625m
Detector Resolution	384x288, 12μm		640x512, 12μm	
Display Resolution	OLED 0.39 1024x768			
NETD	< 35mK (@25°C,F#=1.0)			
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)			
Spectral Response	8-14μm			
Frame Rate	50Hz			
Button Operation	2 Buttons + 1 Dial Switch			
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.			
Digital Zoom	1X-8X Zoom			
Shutter Mode	With Shutter, Auto Shutter mode			
Function Menu	NUC, Crosshair, WIFI Hotspot, Photo and Video Recording, Laser Rangefinder, Removable Battery, Restore Default Settings,Version Information, DDE, Gyroscope, Blind Pixel Calibration, Ballistic Calculation, Accelerometer, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode, Clip-on Mode.			
Battery Capacity	Single Cell 18650 / 3000mAh			
Storage Memory	32G			
Operating Time	3H(Individual Observation Time)			
IP Rating	IP66			
Shock	1000g			
Weight (Including Battery)	550g	578g	550g	578g
IP Rating	134x80x62mm	136x80x62mm	134x80x62mm	136x80x62mm
Housing Material	Metal			
Operating Environment	-20C° ~ + 60C°			



QM Series Thermal Imaging Sight Scope

Product Features

Detector Resolution
640x512 / 1280x1024

Lens
35 / 50 / 60mm

Digital Zoom
1x-8x

Waterproof Rating
IP66

Pixel Pitch
12μm

Frame Rate
50Hz

NETD
< 25mK

Pseudo-color Modes
White Hot , Black Hot,
Red Hot, Iron Red, etc.

Model	QM635	QM650	QM650
Focal Length (mm)	35	50	60
FOV	12.5x10°	8.8x7°	14.6x11.7°
Detection Distance	3500m	5000m	6000m
Recognition Distance	875m	1250m	1500m
Identification Distance	438m	625m	750m
Detector Resolution	640x512, 12μm		1280x1024, 12μm
Display Resolution	OLED 0.6 1280x1024		
NETD	< 25mK (@25°C,F#=1.0)		
Detector Type	Uncooled Focal Plane Array Detector (VOX - Vanadium Oxide)		
Spectral Response	8-14μm		
Frame Rate	50Hz		
Button Operation	3 Buttons + 1 Rotary Encoder		
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.		
Digital Zoom	1X-8X Zoom		
Shutter Mode	Manual, Auto Shutter		
Function Menu	NUC, Digital Filtering and Noise Reduction, Crosshair, WIFI Hotspot, Photo and Video Recording, Laser Rangefinder, Restore Default Settings, Removable Battery, Version Information, DDE, Gyroscope, Blind Pixel Calibration, Ballistic Calculation, Accelerometer, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode, Auto Power-off, Clp-on Mode.		
Battery Capacity	Single Cell 18650 / 3400mAh		
Storage Memory	32G		
Operating Time	5H(Individual Observation Time)		
IP Rating	IP66		
Shock	1000g		
Housing Material	Metal		
Operating Environment	-20C° ~ +60C°		



CE Series Handheld Thermal Imager

Product Features

Detector Resolution
256X192 / 384X288

Lens
10 / 15 / 19 / 25mm

Digital Zoom
1x-8x

Size
180x55mm

Pixel Pitch
12μm

Frame Rate
50Hz

NETD
< 35mK

Pseudo-color Modes
White Hot , Black Hot,
Red Hot, Iron Red, etc.

Model	CE-210	CE-215	CE-315	CE-319	CE-325
Focal Length (mm)	10	15	15	15	25
FOV	17.5x13.2°	11.7x8.8°	17.5x13.2°	13.9x10.4°	10.6x7.9°
Detection Distance	1000m	1500m	1500m	1900m	2500m
Recognition Distance	250m	375m	375m	475m	625m
Identification Distance	125m	188m	188m	258m	313m
Detector Resolution	256x192, 12μm		384x288, 12μm		
Display Resolution	OLED 0.32 800x600		OLED 0.39 1024x768		
NETD	< 35mK(@25°C,F#=1.0)				
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)				
Spectral Response	8-14μm				
Frame Rate	50Hz				
Button Operation	5 Buttons				
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.				
Digital Zoom	1X-8X Zoom				
Shutter Mode	With Shutter, Auto Shutter mode				
Function Menu	NUC, Noise Reduction, CVBS, Crosshair, Wi-Fi Hotspot, Video Recording, Infrared Laser, Hotspot Tracking, Auto Power-Off, Restore Factory Defaults, Version Information, OSD, Blind Pixel Calibration, Probabilistic Ranging, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode.				
Battery Capacity	Single Cell 18650 / 3000mAh				
Storage Memory	32G				
Operating Time	5H(Individual Observation Time)				
IP Rating	IP66				
Power Consumption	≤ 1.5w				
Weight (Including Battery)	389g				
Size	180x55mm				
Housing Material	Plastic				
Operating Environment	-20C° + 60C°				



CE Series Handheld Thermal Imager

Product Features

Detector Resolution	Pixel Pitch
640x512	12μm
Lens	Frame Rate
35 / 50mm	50Hz
Digital Zoom	NETD
1x-8x	< 35mK
Size	Pseudo-color Modes
215x55mm / 235x55mm	White Hot , Black Hot, Red Hot, Iron Red, etc.

Model	CE-635	CE-650
Focal Length (mm)	35	50
FOV	7.5x5.7°	8.8x7°
Detection Distance	3500m	5000m
Recognition Distance	875m	1250m
Identification Distance	438m	625m
Detector Resolution	640x512, 12μm	
Display Resolution	OLED 0.39 1024x768	
NETD	< 35mK (@25°C,F#=1.0)	
Detector Type	Uncooled Focal Plane Array Detector (VOX - Vanadium Oxide)	
Spectral Response	8-14μm	
Frame Rate	50Hz	
Button Operation	5 Buttons	
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.	
Digital Zoom	1X-8X Zoom	
Shutter Mode	With Shutter, Auto Shutter mode	
Function Menu	NUC, Noise Reduction, CVBS, Crosshair, Wi-Fi Hotspot, Video Recording, Infrared Laser, Hotspot Tracking, Auto Power-Off, Restore Factory Defaults, Version Information, OSD, Blind Pixel Calibration, Probabilistic Ranging, PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast, Digital Zoom, Shutter Mode.	
Battery Capacity	Single Cell 18650 / 3000mAh	
Storage Memory	32G	
Operating Time	5H(Individual Observation Time)	
IP Rating	IP66	
Power Consumption	≤ 1.5w	
Weight (Including Battery)	535g	547g
Size	215x55mm	235x55mm
Housing Material	Plastic	
Operating Environment	-20C°~+60C°	



Detector Resolution
384x288 / 640x512

Lens
15 / 19 / 25 / 35mm

Digital Zoom
1x~8x

Size
82x59x56mm / 90x59x56mm

Pixel Pitch
12μm

Frame Rate
50Hz

NETD
< 35mK

Pseudo-color Modes

White Hot , Black Hot,
Red Hot, Iron Red, etc.

[illegible]



XQ Series Handheld Thermal Imager

Product Features

Detector Resolution	Pixel Pitch
384X288 / 640X512	12μm
Lens	Frame Rate
25 / 35 / 50mm	50Hz
Digital Zoom	NETD
1x~8x	< 35mK

Size	Pseudo-color Modes
154x73x44mm / 165x73x44mm 180x73x44mm	White Hot , Black Hot, Red Hot, Iron Red, etc.

Model	XQ325	XQ335	XQ650
Focal Length (mm)	25	35	50
FOV	10.6x7.9°	7.5x5.7°	8.8x7°
Detection Distance	2500m	3500m	5000m
Recognition Distance	625m	875m	1250m
Identification Distance	313m	438m	625m
Detector Resolution	384x288, 12μm		640x512, 12μm
Display Resolution	OLED 0.39 1024x768		
NETD	< 35mK (@25°C,F#=1.0)		
Detector Type	Uncooled Focal Plane Array Detector (VOX - Vanadium Oxide)		
Spectral Response	8~14μm		
Frame Rate	50Hz		
Button Operation	5 Buttons		
Pseudo-color Modes	White Hot (default), Black Hot, Red Hot, Iron Red, etc.		
Digital Zoom	1X-8X Zoom		
Shutter Mode	Manual, Auto Shutter		
Function Menu	NUC, Image Detail Enhancement, Digital Filtering and NoiseReduction, CVBS, Removable Battery, Crosshair, WIFI Hotspot, Photo and Video Recording, Laser Rangefinder, Restore Default Settings, Version Information, Gyroscope, Blind Pixel Calibration,PIP, Mobile App, Bad Pixel Correction, Brightness, Contrast,Digital Zoom, Shutter Mode.		
Battery Capacity	Single Cell 18650 / 3400mAh		
Storage Memory	32G		
Operating Time	5H (Individual Observation Time)		
IP Rating	IP66		
Power Consumption	≤ 1.8w		
Weight (Including Battery)	469g	510g	587g
IP Rating	154x73x44mm	165x73x44mm	180x73x44mm
Housing Material	Metal		
Operating Environment	-20C° ~ +60C°		



HF609-PRO

Dual-Spectral Drone

Product Features

Detector Resolution	Battery
640x512	4200mAh
Gimbal	Video Transmission
Three-axis	Relay Digital Video Transmission
Positioning System	Wind Resistance Level
GNSS / Optical Flow / TOF	Level 6
Size	Pseudo-color Modes
520x440x96mm	White Hot , Black Hot, Red Hot, Iron Red, etc.

Model	HF609-PRO	
Size	Unfolded: 520×440×96mm	
Weight	Approximately 750g (including battery)	
Max Ascend Speed	2.5m/s	
Max Descend Speed	4m/s	
Max Horizontal Flight Speed	9m/s	
Control Range	4 km	
Endurance Time	Hovering Time: 34 min	
	Flight Time: 25 min	
Max Wind Resistance Level	Level 6	
Hovering Accuracy	Vertical: ±0.2m (Visual Mode), ±0.8m (GPS Mode)	
	Horizontal: ±0.3m (Visual Mode), ±1.5m (GPS Mode)	
Gimbal	Stabilization System: Three-axis Brushless Gimbal	
Visible Light Camera	Sensor: Sony IMX586, 48 Megapixels	
	Focal Length: 8mm	
Thermal Imaging Camera	Resolution: 8000x6000	
	Image Format: JPG	
	Video Format: MP4	
	Video Resolution: 4K / 30fps	
Video Transmission	Uncooled VOx (Vanadium Oxide) Sensor: 640x512	
	FOV (Field of View): 46°x38°	
Positioning System	Aperture: f / 1.0	
	Focal Length: 9mm	
Perception System	Image Format: JPG	
	Video Format: MP4	
Battery	5G Relay Digital Video Transmission	
	GNSS / Optical Flow / TOF	
Perception System	Front-view	Rear-view
	Precision Perception Range: 0.3 to 15 meters	Precision Perception Range: 0.3 to 15 meters
Battery	Effective Obstacle Avoidance Speed: ≤ 4m/s	Effective Obstacle Avoidance Speed: ≤ 4m/s
	Field of View: 60°	Field of View: 60°
4200mAh		



AC Series Module

Product Features

Detector Type

Uncooled Focal Plane Array
Detector (VOx - Vanadium Oxide)

Resolution

384x288 / 640x512

Lens

4/9mm

Analog Image Interface

CVBS(PAL Format)

Pixel Pitch

12μm

Frame Rate

50Hz


NETD

≤ 35mK

Pseudo-color Modes

White Hot , Black Hot,
Red Hot, Iron Red, etc.

Model	AC384-4	AC384-9	AC640-4	AC640-9
Focal Length (mm)	4	9	4	9
FOV	59.9x46.7°	28.7x21.7°	87.7x75°	46.2x37.7°
Detection Distance	400m	900m	400m	900m
Recognition Distance	100m	225m	100m	225m
Identification Distance	50m	113m	50m	113m
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)			
Spectral Response	8~14μm			
Resolution	384x288, 12μm		640x512, 12μm	
NETD	≤ 35mK(f / 1.0 50Hz 300K)			
Frame Rate	50Hz			
Analog Video Interface	CVBS(PAL Format)			
Control Interface	UART			
Interface Specification	SMD,P=1.25mm-5P			
Pseudo-color Modes	White Hot , Black Hot, Red Hot, Iron Red, etc			
Image Enhancement Mode	Adjustable			
Brightness / Contrast	Adjustable			
Digital Zoom	1X to 8X zoom			
Shutter Mode	With Shutter, Auto Shutter mode			
Lid Calibration	Supports UART serial communication with user PC (host computer)			
Non-Uniformity Correction (NUC)	Supports UART serial communication with user PC (host computer)			
Power Supply Input	4.5v~27v			
Operating Temperature	-20°c ~ +60°c			
Power Consumption	≤ 1w			
Shock	80g @ 4ms			
Weight	54g			
Dimension	28mmx28mmx38.7mm(subject to the actual product)			
Secondary Development	/			



M2V Series

Dual-ChannelFusion Module

Product Features

Detector Type

Uncooled Focal Plane Array
Detector (VOx - Vanadium Oxide)

Resolution

256 / 384 / 640

Lens

4/9mm

Analog Image Interface

CVBS(PAL Format)

Pixel Pitch

12μm

Frame Rate

50Hz


NETD

≤ 25mK

Pseudo-color Modes

White Hot , Black Hot,
Red Hot, Iron Red, etc.

Model	M2V2		M2V3		M2V6	
Image	Thermal Imaging	Low-Light	Thermal Imaging	Low-Light	Thermal Imaging	Low-Light
Focal Length (mm)	4	6	9.1	6	9.1	6
FOV	42x32.1°	56.1x43.6°	28.4°x21.5°	56.1x43.6°	45.8°x37.3°	56.1x43.6°
Detection Distance	400m	1020m	910m	1020m	910m	1020m
Recognition Distance	100m	340m	228m	340m	228m	340m
Identification Distance	50m	170m	114m	170m	114m	170m
Resolution	256x192, 12μm	Megapixel HD	384x288, 12μm	Megapixel HD	640x512, 12μm	Megapixel HD
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)					
NETD	≤ 25mK(f/1.0 50Hz 300K)					
Spectral Response	8~14μm					
Frame Rate	50Hz					
Analog Video Interface	CVBS(PAL Format)					
Control Interface	UART					
Interface Specification	SMD,P=1.25mm-5P					
Pseudo-color Modes	White Hot, Black Hot, Red Hot, Iron Red, etc.					
Mode Selection	Fusion (default), Low-Light, Thermal, etc.					
Fusion Mode	Forest, Urban, etc.					
Edge Outline Selection	Supports Multiple Color Adjustments					
Infrared Fusion Ratio	Supports Multiple Level Adjustments					
Low-Light Detail Weight	Supports Multiple Level Adjustments					
Lid Calibration	Supports Serial Communication Protocol					
Non-Uniformity Correction (NUC)	Supports Serial Communication Protocol					
Power Supply Input	4.5v ~ 27v					
Operating Temperature	-20℃ ~ +60℃					
Power Consumption	≥ 1.5w					
Dimension	39x21x44.5 mm(including lens and connector)					
Weight	46.5g					



UV Series Module

Product Features

Detector Type
Uncooled Focal Plane Array
Detector (VOx - Vanadium Oxide)

Resolution
256 / 384 / 640

Lens
4/9mm

Analog Video interface
USB,UVC


Pixel Pitch
12μm

Frame Rate
50Hz

NETD
≤ 25mK

Pseudo-color Modes
White Hot , Black Hot,
Red Hot, Iron Red, etc.

Model	UV256-4	UV256-9	UV384-4	UV384-9	UV640-4	UV640-9
Focal Length (mm)	4	9	4	9	4	9
FOV	42x32.1°	19.4x14.6°	59.9x46.7°	28.7x21.7°	87.7x75°	46.2x37.7°
Detection Distance	400m	900m	400m	900m	400m	900m
Recognition Distance	100m	225m	100m	225m	100m	225m
Identification Distance	50m	113m	50m	113m	50m	113m
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)					
Spectral Response	8-14μm					
Resolution	256x192, 12μm		384x288, 12μm		640x512, 12μm	
NETD	≤ 25mK(f / 1.0 50Hz 300K)					
Frame Rate	50Hz					
Analog Video Interface	USB, UVC					
Control Interface	USB					
Interface Specification	SMD, P=0.8mm-4P					
Pseudo-color Modes	White Hot , Black Hot, Red Hot, Iron Red, etc.					
Image Enhancement Mode	Adjustable					
Brightness / Contrast	Adjustable					
Digital Zoom	1X to 8X zoom					
Shutter Mode	With Shutter, Auto Shutter mode					
Lid Calibration	Supports USB serial communication with user PC (host computer)					
Non-Uniformity Correction (NUC)	Supports USB serial communication with user PC (host computer)					
Power Supply Input	USB(5V)					
Operating Temperature	-20℃ ~ +60℃					
Power Consumption	≤ 0.8w					
Shock	80g @ 4ms					
Weight	23g					
Dimension	21mmx21mmx29.8mm(subject to the actual product)					
Secondary Development	Supports Windows, Linux, and Android, with an SDK available for secondary development					



CV Series Module

Product Features

Detector Type

Uncooled Focal Plane Array
Detector (VOx - Vanadium Oxide)

Resolution

256 / 384 / 640

Lens

4/9mm

Analog Video interface

CVBS(PAL Format)

Pixel Pitch

12μm

Frame Rate

50Hz


NETD

≤ 25mK

Pseudo-color Modes

White Hot, Black Hot

Model	CV256-4	CV256-9	CV384-4	CV384-9	CV640-4	CV640-9
Focal Length (mm)	4	9	4	9	4	9
FOV	42x32.1°	19.4x14.6°	59.9x46.7°	28.7x21.7°	87.7x75°	46.2x37.7°
Detection Distance	400m	900m	400m	900m	400m	900m
Recognition Distance	100m	225m	100m	225m	100m	225m
Identification Distance	50m	113m	50m	113m	50m	113m
Detector Type	Uncooled Focal Plane Array Detector (VOx - Vanadium Oxide)					
Spectral Response	8-14μm					
Resolution	256x192, 12μm		384x288, 12μm		640x512, 12μm	
NETD	≤ 25mK(f / 1.0 50Hz 300K)					
Frame Rate	50Hz					
Analog Video Interface	CVBS(PAL Format)					
Control Interface	UART					
Interface Specification	SMD,P=1.25mm-5P					
Pseudo-color Modes	White Hot, Black Hot					
Image Enhancement Mode	Adjustable					
Brightness / Contrast	Adjustable					
Digital Zoom	1X to 8X zoom					
Shutter Mode	With Shutter, Auto Shutter mode					
Lid Calibration	Supports UART serial protocol					
Non-Uniformity Correction (NUC)	Supports UART serial protocol					
Power Supply Input	4.5v-18v					
Operating Temperature	-20℃ ~ +60℃					
Power Consumption	≤ 0.8w					
Shock	80g @ 4ms					
Weight	23g					
Dimension	21mmx21mmx29.8mm(subject to the actual product)					
Secondary Development	/					

[illegible]



7 Vehicle-Mounted Thermal Imaging

Product Features


Resolution 256x192	Pixel Pitch 12μm
Lens 10mm	Frame Rate 25Hz
FOV 18x13°	NETD 50mK
Display Screen Size 7 Inches	Alarm Method Built-in Speaker Alarm

Model	L7 Vehicle-mounted Thermal Imaging
	Thermal Imaging Camera Parameters
Spectral Response Range	8~14μm
NETD	50mk
Resolution	256x192
Pixel Pitch	12μm
Lens	10mm
FOV	18x13°
Frame Rate	25Hz
	Display Unit Parameters
Dimension	7 Inches
Resolution	1024x600
System	LINUX
Recognition Type	People and Vehicles
Recognition Rate	≥ 95 %
GPS	Built-in
Alarm Mode	Built-in Speaker Alarm
	Other Parameters
Lens Protection	High-strength Protective Window
Window Defrosting	Aluminum Alloy Housing, IP67 Sealed
Size	40x30x26mm
Weight	About 100g
Operating Voltage	9~24V
Power	5W
Main Unit Dimensions	180x30x117mm
Weight	360g

APPLICATION SCOPE



Hunfing



Wildlife Monitoring



Camping



Search & Rescue



Drone Inspection

Tel: +86-0755- 86271863

Web: www.cethermal.com

E-mail: sales@cethermal.com

Add : Room 1406, Building 1 Xunmei Technology Plaza No. 8 Keyuan Road Yuehai Subdistrict Nanshan District Shenzhen